



# **secunet Security Networks AG**

## **Experiences with the retraining of NFIQ**

Gaithersburg, **March 1st, 2010**

Markus Nuppeney, Bundesamt für Sicherheit in der Informationstechnik (BSI)

Dr. Johannes Merkle, secunet Security Networks AG

Marco Breitenstein, secunet Security Networks AG

# Agenda

---

1

Why retrain NFIQ?

2

Training approach and results

2

Wrap-up / discussion of next steps

# Why retrain the NFIQ?

## Widely used reference

- Recognized as a reference in fingerprint quality estimation
- Used for ePassport application e.g. in Germany
- Used for Visa application e.g. in Germany
- Often coded as quality estimate in fingerprint reference data
- Seen as a reference compared to alternative approaches


## Potential improvements

- Strange behaviour in some cases
  - E. g. quality values for fingertips only
- Increase speed
- More granular quality estimation
  - Definition of more classes
  - More homogenous distribution of classes
- Better suited training base for the target application
  - E.g. no rolled or paper scanned fingerprints for eDocuments


# General Approach

---


## Statistical Evaluation



## Estimation by Neural Network



# Thoughts on influences and parameters for the retraining



## Main changes in BSI/secunet retraining

↓

Different database  
(live scan, plain)

↓

Up-to-date  
matcher


↓

Increase no. of  
classes (10)

**secunet**


# Data basis

- Original NFIQ used several databases
  - Both live-scans and inked imprints → Inked imprints not relevant for border control
  - two imprints per finger → only one genuine score per finger
  - 50% as training set, 50% as test set
- We used 9 live-scans of 8784 fingers, captured with 3 different sensors
  - 8 genuine scores per finger
    - allows careful consideration of genuine score deviation by robust measures (15% quantil)
  - Computation of 450 match scores per imprint
- We used 5 matching algorithms
  - NIST, Neurotechnology, L1/Identix, Dermalog, NEC
  - NEC SDK returns match score „0“ in case of non-match (internal threshold)
    - match score statistics less significant
- 5 classes, resembling original NFIQ




# Result

- Impact of neural network training parameters were small
- Evaluation on test-set shows slight improvement



- DET curves for fingerprint selection based on NFIQ+ and NFIQ algorithms
- As reference, DET curve of selector based on real classes

# Promising optimization potential



- DET curves show: 10 classes bear more potential than 5
- Optimize class definition first
- Feature vector definition could have great optimization potential
  - E.g. apply neural network for quality assessment of minutiae



# Lessons learned

---

- Retraining is possible ..
- But: No ready to use toolbox
  
- Documentation should be extended for NFIQ 2.0
  - Detailed documentation of the training process is missing
  - Information needs to be gathered by source code examination
  - Results of the original NFIQ training process are not available in detail
    - would be useful for comparing results
  
- Big improvement of NFIQ performance seems to be possible
  - More examination necessary

## Wrap-up

---



NFIQ is highly needed



Clear potential for optimization



NIST's ideas for NFIQ 2.0 highly appreciated



Vendor-independent but modular NFIQ upgrade suggested



Looking forward to an interesting discussion



**Thank you for your attention!**

**secunet Security Networks AG**

Marco Breitenstein

Head of Biometrics & eIDs

+49 201 5454-3019

[marco.breitenstein@secunet.com](mailto:marco.breitenstein@secunet.com)